

Solidfloor™ ...forever yours



CE
EN 14342-05



Lifestyle Caddo PEFC

15/4, 1900x190mm, Oak



PRODUCT MEASUREMENTS

Pieces per pack:	6 pieces
M ² per pack	2,166m ²
Weight per pack:	20kg
Split lengths per pack:	16,7% minimal 60cm long

SIZE TOLERANCES ACC EN 13489

Length:	± 0,2%
Width:	± 0,2mm
Thickness:	Total: 15mm ± 0,2mm Facelayer: 3,5-4,0mm
Lipping (between elements):	≤0,2mm
Squareness:	≤0,2% over the width
Cup:	≤0,2% over the width
Spring:	≤0,1% over the length
Bowing:	<1% of the length

OTHER SPECIFICATIONS

Formaldehyde emission:	E1
Thermal insulation value:	R=0,115m ² k/w
Brinell hardness:	average HB 3.7
Connection:	T&G

ADDITIONAL SPECIFICATIONS

Bevel: 1 mm
Construction: 3-ply

INSTRUCTIONS AND MAINTENANCE

Oxidative oil; Immediately oiling after installation

Maintenance:

Solidfloor™ Ultimate Hardwax Natural &

Solidfloor™ Woodcleaner

Suitable for floor heating & cooling

(see www.solidfloor.com)