

## Lifestyle Orlando FSC



15/4, 2200x260mm, Oak



### PRODUCT MEASUREMENTS

Pieces per pack:	4 pieces
M <sup>2</sup> per pack	2,288m <sup>2</sup>
Weight per pack:	20kg
Split lengths per pack:	25% minimal 60cm long

### SIZE TOLERANCES ACC EN 13489

Length:	± 0,2%
Width:	± 0,2mm
Thickness:	Total: 20mm ± 0,2mm Facelayer: 5,5-6,0mm
Lipping (between elements):	≤0,2mm
Squareness:	≤0,2% over the width
Cup:	≤0,2% over the width
Spring:	≤0,1% over the length
Bowing:	<1% of the length

### OTHER SPECIFICATIONS

Formaldehyde emission:	E1
Thermal insulation value:	R=0,115m <sup>2</sup> k/w
Brinell hardness:	average HB 3.7
Connection:	T&G

### ADDITIONAL SPECIFICATIONS

Bevel: 1 mm 4 sides  
Construction: 3-ply  
Reactive stain

### INSTRUCTIONS AND MAINTENANCE

Lacquered; Oiling after installation not necessary  
Maintenance:  
Solidfloor™ Woodcleaner  
Suitable for floor heating & cooling  
(see [www.solidfloor.com](http://www.solidfloor.com))