

Solidfloor™ ...forever yours



Lifestyle Montgomery FSC

15/4, 2200x260mm, Oak



PRODUCT MEASUREMENTS

Pieces per pack:	4 pieces
M ² per pack	2,288m ²
Weight per pack:	20kg
Split lengths per pack:	25% minimal 60cm long

SIZE TOLERANCES ACC EN 13489

Length:	± 0,2%
Width:	± 0,2mm
Thickness:	Total: 20mm ± 0,2mm Facelayer: 5,5-6,0mm
Lipping (between elements):	≤0,2mm
Squareness:	≤0,2% over the width
Cup:	≤0,2% over the width
Spring:	≤0,1% over the length
Bowing:	<1% of the length

OTHER SPECIFICATIONS

Formaldehyde emission:	E1
Thermal insulation value:	R=0,115m ² k/w
Brinell hardness:	average HB 3.7
Connection:	T&G

ADDITIONAL SPECIFICATIONS

Bevel: 1 mm 4 sides
Construction: 3-ply
Reactive stain

INSTRUCTIONS AND MAINTENANCE

Lacquered; Oiling after installation not necessary
Maintenance:
Solidfloor™ Woodcleaner
Suitable for floor heating & cooling
(see www.solidfloor.com)