



new Classics Canterbury

15/4, 610x122mm, Oak



PRODUCT MEASUREMENTS

Pieces per pack:	12 pieces
M ² per pack	0,893m ²
Weight per pack:	9kg
Split lengths per pack:	Not Allowed

ADDITIONAL SPECIFICATIONS

Bevel: 1 mm 4 sides
 Construction: plywood
 Reactive stain
 Glued installation

SIZE TOLERANCES ACC EN 13489

Length:	± 0,1%
Width:	± 0,2mm
Thickness:	Total: 15mm ± 0,2mm Facelayer: 3,5-4,0mm
Lipping (between elements):	≤0,2mm
Squareness:	≤0,1% over the width
Cup:	≤0,3% over the width
Spring:	≤0,1% over the length
Bowing:	<0,6% of the length

INSTRUCTIONS AND MAINTENANCE

UV oil; Oiling after installation not necessary
 Maintenance:
 Solidfloor™ Ultimate Hardwax Natural &
 Solidfloor™ Woodcleaner
 Suitable for floor heating & cooling
 (see www.solidfloor.com)

OTHER SPECIFICATIONS

Formaldehyde emission:	E1
Thermal insulation value:	R=0,115m ² k/w
Brinell hardness:	average HB 3.7
Connection:	T&G