



**Nevada**  
1204407  
15/4 mm  
1900 x 190 mm

25 years  
guarantee  
**Solidfloor™**



## Packaging

Layers per pack	8 pieces
m <sup>2</sup> per pack	2,888 m <sup>2</sup>
Weight per pack	24 kg
Split lengths per pack	25% minimal 60 cm long

## Size tolerances conform EN13489

Length	0,1%
Width	0,2 mm
Thickness	Total: 15 mm ± 0,2 mm Face layer: 3,5-4,0 mm

Lipping (between the panels)	≤0,2 mm
Squareness	≤0,2% over the width
Cupping	≤0,2% over the width
Spring	≤0,1% over the length
Bowing	<1% over the length

## Other Specifications

Formaldehyde emission	E1
Thermal insulation	R=0,115m <sup>2</sup> k/w
Brinell hardness	Average HB 3.7
Connection	T&G

## Additional specifications

Bevel	rounded
Construction	3-layer

## Instructions and maintenance

Oxidative oil	Immediately oiling after installation
---------------	---------------------------------------

Maintain with Solidfloor™ Ultimate Hardwax White & Solidfloor™ Woodcleaner. Suitable for floor heating & cooling (see [www.solidfloor.com](http://www.solidfloor.com)).

